

09-25-00

PTO
S. U. 13181C
66889/60

00/22/00

Please type a plus sign (+) inside this box → ☐

PTO/SB/05 (08-00)

Approved for use through 10/31/2002. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

**UTILITY
PATENT APPLICATION
TRANSMITTAL**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.

135614

First Inventor

Sharma, et al.

Title

Method and Apparatus for Self-Adjustable...

Express Mail Label No.

EE088739540US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☒ Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☐ Applicant claims small entity status.
See 37 CFR 1.27.
3. ☒ Specification [Total Pages 23]
(preferred arrangement set forth below)
 - Descriptive title of the invention
 - Cross Reference to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to sequence listing, a table, or a computer program listing appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
4. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 7]
5. Oath or Declaration [Total Pages 3]
 - a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 CFR 1.63 (d))
(for continuation/divisional with Box 17 completed)
 - i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
6. ☐ Application Data Sheet. See 37 CFR 1.76

ADDRESS TO:Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

7. ☐ CD-ROM or CD-R in duplicate, large table or Computer Program (Appendix)
8. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - a. ☐ Computer Readable Form (CRF)
 - b. Specification Sequence Listing on:
 - i. ☐ CD-ROM or CD-R (2 copies); or
 - ii. ☐ paper
 - c. ☐ Statements verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

9. ☒ Assignment Papers (cover sheet & document(s))
10. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) ☐ Power of Attorney
11. ☐ English Translation Document (if applicable)
12. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
13. ☒ Preliminary Amendment
14. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
15. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
16. ☐ Other:

17. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment, or in an Application Data Sheet under 37 CFR 1.76:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP)

of prior application No.:

Prior application information.

Examiner

Group / Art Unit:

For CONTINUATION OR DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 5b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.**18. CORRESPONDENCE ADDRESS**☐ Customer Number or Bar Code Label

(Insert Customer No. or Attach bar code label here)

or ☒ Correspondence address below

Name	Alcatel USA				
Address	Intellectual Property Department 1000 Coit Road, MS LEGL2				
City	Plano	State	TX	Zip Code	75075
Country	USA	Telephone	972-477-9109	Fax	972-477-9328

Name (Print/Type)

Jessica W. Smith

Registration No. (Attorney/Agent)

39,884

Signature

Jessica W. Smith

Date 9/22/00

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PATENT APPLICATION FEE DETERMINATION RECORD

Application or Docket Number

135614

CLAIMS AS FILED - PART I

(Column 1)

(Column 2)

SMALL ENTITY

OR

OTHER THAN
SMALL ENTITY

FOR	NUMBER FILED	NUMBER EXTRA
BASIC FEE (37 CFR 1.16(a))		
TOTAL CLAIMS (37 CFR 1.16(c))	14 minus 20 =	* 0
INDEPENDENT CLAIMS (37 CFR 1.16(b))	2 minus 3 =	* 0
MULTIPLE DEPENDENT CLAIM PRESENT (37 CFR 1.16(d))		

RATE	FEE
	\$
x \$	
x	
+	
TOTAL	

RATE	FEE
	\$690.00
x \$ 18.00	
x 78.00	
+	
TOTAL	690.00

* If the difference in column 1 is less than zero, enter "0" in column 2

CLAIMS AS AMENDED - PART II

(Column 1)

(Column 2)

(Column 3)

SMALL ENTITY

OR

OTHER THAN
SMALL ENTITY

AMENDMENT A	CLAIMS REMAINING AFTER AMENDMENT	HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA
Total (37 CFR 1.16(c))	*	Minus **	=
Independent (37 CFR 1.16(b))	*	Minus ***	=
FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(d))			

RATE	ADDITIONAL FEE
x \$	
x	
+	
TOTAL	
ADDITIONAL FEE	

RATE	ADDITIONAL FEE
x \$	
x	
+	
TOTAL	
ADDITIONAL FEE	

(Column 1)

(Column 2)

(Column 3)

ADDITIONAL FEE

ADDITIONAL FEE

AMENDMENT B	CLAIMS REMAINING AFTER AMENDMENT	HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA
Total (37 CFR 1.16(c))	*	Minus **	=
Independent (37 CFR 1.16(b))	*	Minus ***	=
FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(d))			

RATE	ADDITIONAL FEE
x \$	
x	
+	
TOTAL	
ADDITIONAL FEE	

RATE	ADDITIONAL FEE
x \$	
x	
+	
TOTAL	
ADDITIONAL FEE	

(Column 1)

(Column 2)

(Column 3)

ADDITIONAL FEE

ADDITIONAL FEE

AMENDMENT C	CLAIMS REMAINING AFTER AMENDMENT	HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA
Total (37 CFR 1.16(c))	*	Minus **	=
Independent (37 CFR 1.16(b))	*	Minus ***	=
FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(d))			

RATE	ADDITIONAL FEE
x \$	
x	
+	
TOTAL	
ADDITIONAL FEE	

RATE	ADDITIONAL FEE
x \$	
x	
+	
TOTAL	
ADDITIONAL FEE	

* If the entry in column 1 is less than the entry in column 2, write "0" in column 3.

** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 20, enter "20".

*** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 3, enter "3".

The "Highest Number Previously Paid For" (Total or Independent) is the highest number found in the appropriate box in column 1.

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case.
Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO Assistant Commissioner for Patents, Washington, DC 20231.

Applicant(s): Sharma, et al.
Serial No.: Not Assigned
Filed: September 20, 2000

Title: Method and Apparatus for Self-Adjustable Design for Handling Event Flows

PRELIMINARY AMENDMENT

IN THE SPECIFICATION

-- PRIORITY STATEMENT UNDER 35 U.S.C. § 119(e) and 37 C.F.R. § 1.78

REMARKS

Page 1
Preliminary Amendment

Respectfully submitted,

Jessica Smith

Jessica W. Smith

Reg. No. 39,884

Attorney for Applicants

Date: 9/22/00

Alcatel USA
Intellectual Property Department
1000 Coit Road, MS LEGL2
Plano, TX 75075
Telephone (972) 477-9109; Facsimile (972) 477-9328

Certificate Under 37 C.F.R. § 1.8(a)

I hereby certify that the above correspondence is being deposited with the U.S. Postal Service as First Class Mail in an envelope addressed to: Assistant Commissioner of Patents, Washington, D.C. 20231 on September 22, 2000.

By: Melanie Murdock
Melanie Murdock, Legal Assistant

TITLE

**METHOD AND APPARATUS FOR SELF-ADJUSTABLE DESIGN
FOR HANDLING EVENT FLOWS**

INVENTORS

SANDEEP SHARMA
620 Uvalde Court
Allen, Texas 75013
Citizenship: India

WEI WEI
8620 Mill Creek Road
Irving, Texas 75063
Citizenship: China

PHILLIP HEISLER
3200 Jomar Drive
Plano, Texas 75075
Citizenship: USA

ASSIGNEE

ALCATEL USA SOURCING, L.P.
1000 Coit Road
Plano, Texas 75075

Certificate Under 37 C.F.R. § 1.8(a)

I hereby certify that the above correspondence is being deposited with the U.S. Postal Service in an envelope addressed to: Assistant Commissioner of Patents, Box Patent Application, Washington, D.C. 20231 on September 22, 2000.

Express Mail Label: EE088739540US

By: Melanie Murdock
Melanie Murdock, Legal Assistant

**TITLE: METHOD AND APPARATUS FOR SELF-ADJUSTABLE DESIGN
HANDLING EVENT FLOWS**

SPECIFICATION

BACKGROUND

1. Technical Field

5 The present invention relates generally to data transmission in data communication networks, by way of example, the synchronous optical networks, (SONET networks) and Synchronous Digital Hierarchy networks (SDH networks) and more particularly to the control of alarm messages within a network to prevent the excessive generation of alarm messages from degrading network performance.

2. Related Art

10 New networks and information exchange capabilities that were unimaginable even in recent times are being developed and implemented in a way that impacts businesses and individuals in a significant way. For example, desktop computers may now be integrated with wireless radio telephones to allow the transmission of information from the computer to a destination by way of a land line communication network and then by way of a wireless communication network.

15 The recent explosion of the internet is creating the capability and desire for networks of all types to be integrated and coupled to exchange data signals carrying varying types of information. In many cases, the same data will be transported through a local area network prior to being delivered to the internet. Thus, by way of example, a digital signal can be transported from a source through a local area network and through the internet to a final destination. Moreover, within the internet portion itself, there may be a need to transport the user data through a backbone data transfer port infrastructure, by way of example, through a

fiber optic ring network. The aforementioned SONET and SDH networks play a key role in providing a backbone data transport infrastructure.

Generally speaking, the internet itself is in essence a collection of many large and small computer networks that are coupled together over high speed backbone data links such as T-1, T-3, OC-1 and OC-3. Stated differently, the internet is a network of networks. As a result of the creation of the internet, worldwide access may be achieved. People and their equipment may now communicate from most any civilized point to another in a fast and relatively inexpensive medium.

In order to make communication devices created by companies throughout the world compatible with each other to create local area networks and worldwide networks such as the internet protocols and standards are often defined. These protocols and standards are used to guide the design of the communication devices, and more specifically, to guide the design of the operating logic in software within the devices. While communication devices that are designed in view of these standards do not always follow the suggested models exactly, they are usually compatible with the protocol-defined interfaces (physical and logical).

Regarding its physical aspects, the internet is a packet switched network that is currently based on a group of protocols for exchanging data. For example, a transmission control protocol/internet protocol (TCP/IP) is a connection-oriented protocol that first establishes connection between two computer systems that are to exchange data. The digital information is then broken into data packets having a defined format. The packets are attached to headers that are for containing control and address information and are transmitted through the internet and through the back hall infrastructures.

Many of the common backbone data transport systems utilized include time division multiplexed (TDM) double ring transmission systems. Double ring TDM systems are generally known, especially for fiber optic communication networks. In order to maintain transmission

in the event of a fault on one of the channels of the communication links, it is typically common to find ring transmission systems in which transmissions occur in two directions. Specifically, transmissions occur in one direction through all of the nodes in the ring in a working path in through an opposite direction in a protection path.

5 The protection path is, traditionally, a redundant path for transmitting signals in a failure condition. Examples of fiber optic TDM systems include the SONET and SDH double ring fiber optic communication systems used in North American and Europe, respectively. As a result of the internet, many types of networks that traditionally have been independent of one another are now being integrated so that a user of one type of device may relay messages to another type of device.

10 By way of example, networks are being integrated to allow a user of a computer to generate a message that is transmitted to a recipient's cellular phone. By way of example, the sender might enter a message upon his computer, then use the public switch telephone network to access the internet wherein the message is transmitted to a paging company that in turn utilizes a cellular network to deliver a text message to the recipient.

15 In the described example, three different networks were utilized to deliver the message. The internet formed the backbone network that tied the public switched telephone network to the wireless network to deliver the message. Moreover, had that user been on a computer terminal that is part of a corporate LAN, by way of example, then the message would have had to be transmitted through the corporate LAN prior to being transmitted over the public switch telephone network and then the internet and then the wireless network.

20 Because the internet and demand for internet access has exploded, the aforementioned data transport networks for providing a data backhauling have been developed to conduct large numbers of communication channels and large amounts of data. Fiber optic networks, in particular, are very attractive for backhauling data because they have achieved very high

capacity rates. One fiber optic strand alone can carry dozens of times more data than a traditional wire line. Because a fiber optic cable comprises a bundle of many such strands, the data throughput capacity of modern fiber optic networks is enormous.

As these networks evolve and progress, the control of the networks is developed at many different layers or levels of abstraction. For example, the OSI model defines seven (7) layers of protocol for data transport and control of the same. Needless to say, the software and systems that are required to merely control such large amounts of data form their own networks that are also very sophisticated and have significant feedback mechanisms to enable precise control.

For one example, an element management system may receive feedback on network conditions from up to 250 cross connect systems that are used for routing and controlling data flow. Each of the 250 cross connect systems, in turn, may control up to 8,000 logical communication lines in a data pipeline network. Thus, significant amounts of error messages may be generated when a problem is detected by one of the 250 cross connect devices.

More specifically, network management systems can operate under degraded conditions or even crash when an event occurs that causes at least one network element to generate large numbers of messages, alarms and other signals to the event. The results from a surge of alarms (hereinafter event flow) may lead to problems ranging from system degradation to actual system crash. What is needed therefore is a system and method for preventing an event flow from degrading or crashing the system or network.

SUMMARY OF THE INVENTION

To overcome the shortcomings of the prior systems and their operations, the present invention contemplates an apparatus and a method for limiting the number of specified messages placed onto a network thus to improve network performance. More specifically, in the occurrence of an event that prompts a network element to generate a large number of non-critical alarms, an element management system, upon detecting that a defined threshold has been exceeded for specified types of messages, determines which network element is generating the greatest number of such messages. Thereafter, the element management system then instructs the network element that is generating the largest number of alarm messages to cease transmitting a specified type of alarm message.

By way of example, in some cross connect network elements, there are a great number of quality of service oriented signals and alarms that may be generated by the cross connect network element. Among these, there are 33 signals, for one particular cross connect network element, that specify when a defined threshold has been reached. In addition to the threshold type of quality of service signals, there are others as well.

Accordingly, the invention contemplates having the element management system that instruct the cross connect network elements to suspend transmitting specific types of QoS threshold alarms. In an alternate embodiment of the invention, if the event flow rate is still too high, the element management system may instruct the cross connect network element to stop sending all threshold types of alarms. Finally, if the event flow rate is still too high, the element management system may cause all QoS alarms from the one network element to not be transmitted. Alternatively, the threshold alarms from other network elements may be muted for a period to reduce the overall event flow rate. For each of these scenarios, the element management system suspends the flow of messages for a defined period of time. For example, in one preferred embodiment, the select type of QoS signal is muted for a period of 600

seconds. In an alternate embodiment of the invention, a network element is allowed to start transmitting the suspended QoS signals if the overall alarm rate for the suspended QoS signals falls below a lower threshold value. In the preferred embodiment of the invention, the upper threshold is 10 events per second for all network elements or 1 per second for any one network element. In this alternate embodiment, the lower threshold is 3 events per second for all network elements.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGURES 1A and 1B are functional block diagrams illustrating a plurality of data transport networks and a control network for controlling the data transport within the data transport networks according to a preferred embodiment of the invention;

FIGURE 2 includes a curve that illustrates network operation according to one embodiment of the invention in terms of the rate of alarm transmissions versus time;

FIGURE 3 is a state transition diagram illustrating two modes of operation for a cross connect network element within a wide area control network 100 of FIGURE 1;

FIGURE 4 is a flow chart illustrating a method for controlling an event rate to avoid system degradation according to a preferred embodiment of the invention;

FIGURE 5 is a flow chart illustrating the method in which the element management system monitors the event rate according to one embodiment of the invention;

FIGURE 6 is a flow chart illustrating an alternate embodiment for reducing the rate of event flows, namely the rate of QoS alarms that are transmitted to the element management system; and

FIGURE 7 is a flow chart that illustrates an alternate embodiment of an inventive method for reducing an event flow rate in a network.

DETAILED DESCRIPTION OF THE DRAWINGS

FIGURES 1A and 1B are functional block diagrams illustrating a plurality of data transport networks and a control network for controlling the data flow within the data transport networks. Referring now to FIGURES 1A and 1B, a wide area control network 100 is coupled to communicate with a plurality of data transport networks 150. More specifically, a network management system 102 is coupled to exchange control signals with an element management system 104. Element management system 104 is coupled to exchange control signals and to receive network information from each of a plurality of cross connect network elements. For example, cross connect network element 106A is shown transmitting a quality of service signal 108 to element management system 104.

Element management system 104 includes a processor 104A, a store 104B and a memory 104C and a transceiver port 104D. Transceiver port 104D is for enabling the element management system 104 to communicate with a plurality of network elements 106. For example, in one embodiment of element management system 104, transceiver 104D is operable to communicate with 250 network elements 106 over a wide area network. Processor 104A is operable to execute computer instructions stored within store 104B. The computer instructions 104B define the operation and operational logic of the element management system 104 according to the present invention. For example, the computer instructions within store 104B define the logic to prompt one or more network elements to stop transmitting alarms as described herein. More particularly, the method steps described in each of the following figures that are performed by an element management system 104 are defined in the computer instructions stored within store 104B. For example, each method step relating to the logic for determining which alarms are to be muted and for how long is defined in store 104B.

Each element management system 104, in the described embodiment, is capable of communicating with and up to 250 cross connect network elements over wide area control

network 100. As may be seen, therefore, the element management systems must be capable of communicating with many cross connect network elements at once. Should an event occur to cause some of the cross connect network elements 106A to generate a large number of QoS signals 108, the network operation may become degraded especially if there are many other ongoing communications.

Each of the cross connect network elements 106A and 106B are connected to their own data transport networks 150A and 150B, respectively. Each of the data transport networks 150A and 150B shown here in FIGURES 1A and 1B is a dual ring SONET network. It is understood, of course, that the invention is not limited to any particular data transport network and, more specifically, to dual ring SONET networks.

Continuing to refer to FIGURES 1A and 1B, cross connect network element 106A includes an interface port 110 for communicating with element management system 104. Additionally, cross connect network element 106A includes an internal bus to enable communications between a processor 114, a store 116, and a memory 118. Store 112 is a memory device, typically formed of a hard disk, that includes computer instructions that define the operational logic for cross connect network element 106A. Memory 118 is formed, in the preferred embodiment, of a disk as well. Because its purpose is for storing data on a temporary basis, however, other known types of memory may be used including random access memory. Processor 110 communicates with store 116 over internal bus 116 to obtain and execute the stored computer instructions. Additionally, processor 114 communicates with memory 118 over bus 116 to place data within the memory that is to be used as part of the operations. Internal bus 116 also is coupled to bus interface 120 which serves to interface a large plurality of ports X1 through Xn. Network element 106A communicates with cross connect network elements.

As stated before, one cross connect network element may control up to 8,000 virtual communication links. Accordingly, significant interface capabilities are required between the cross connect network element 106A and the data transport network 150A.

The computer instructions stored within store 116 also define logic to create an event forwarding discriminator 122 and a plurality of managed objects. Herein FIGURES 1A and 1B, managed objects O1, O2 and O3 are shown at 124A-124C, respectively. Each managed object represents a specified function or grouping of computer instructions that perform a specified function. As is known by those skilled in the art, each of the managed objects O1, O2 and O3 as well as the event forwarding discriminator (EFD) 122 are addressable as distinct devices of a network. Thus, element management system 104 is capable of transmitting specified commands to the EFD or to the managed objects 124A-124C.

In operation, processor 114 interprets a command having a specified address, for example, one that is intended for EFD 122, and then executes an algorithm that is called by or relates to the specified address given in the command from element management system 104. By way of example, if element management system 104 generates a message to instruct the EFD to filter a specified type of quality of service signal in response to receiving too many quality of service alarms, processor 114 will execute a series of computer instructions that achieve the effect desired by element management system 104. In the described embodiment, each of the managed objects send alarms to EFD 122. EFD 122 analyzes the received alarms and decides which alarms to forward to the network element management system 104. Thus, element management system 104 may generate instructions for a specified managed object such as managed object 124A or for the EFD 122 to stop sending specified types of alarms.

Store 116 also includes computer instructions to limit the transmission of specified types of quality of service signals or alarms under specified conditions. For example, in one embodiment, the computer instructions stored within store 116 enable the cross connect

network element 106 to store in memory a specified quality of service signal when so instructed by the element management system 104. If the cross connect network element 106 continues to send too many alarms, then the logic within store 116 also is capable of muting all quality of service threshold alarms, and then if necessary, all alarms. In the preferred embodiment, each alarm that is prevented from being transmitted over a bus to element management system 104 is stored in memory 118 until such time that element management system 104 requests an upload of all stored alarms. Thus, as may be seen, store 116 also includes computer instructions that define logic for responding to a request to upload stored alarms.

Continuing to refer to FIGURES 1A and 1B, it may be seen that the network management system 102 is coupled to an operator console 102a. The operator console 102a is for allowing an individual to interact with the network management system 102 to specify the upper and lower thresholds that trigger the state changes as defined herein. For example, an operator may enter, for some embodiments, just the upper threshold value that triggers a 600 second suspension. For example, if the operator determines that the event flow rate is still typically too high after 600 seconds, the operator might choose to increase that value to another number, by way of example, 900 seconds. Alternatively, if the operator determines that 600 seconds always is enough, then she might experiment by reducing the suspension period to a lower number such as 300 seconds. Accordingly, the ability to specify the suspension period allows the system to be tuned and adjusted to a period of time that typically works well but that minimizes the suspension period. Alternatively, the operator console 102 may also enable then operator to specify the actual threshold values if the operator determines that they may be changed. Thus, by way of example, the upper threshold value may be set to an event flow rate of 30 events per second instead of 10 events per second. Thus, the selected threshold values and/or the selected suspension period values are transmitted in a system parameters signal 102b

from console 102a to network management system 102 which in turn transmits a signal containing the information of signal 102b to element management system 104.

FIGURE 2 includes a curve that illustrates network operation according to one embodiment of the invention in terms of the quantity of alarm transmissions versus time. More specifically, FIGURE 2 illustrates an event rate flow for quality of service messages. In modern networks, a very large number of quality of service messages are often defined to enable an element management system to properly control the various networks. For example, there are 33 types of threshold crossing alerts that are defined for this one existing cross connect network element. Thus, for exemplary purposes, FIGURE 2 illustrates a curve that represents the rate of the threshold crossing alerts that are received by the element management system 104 of FIGURE 1.

As may be seen, referring to FIGURE 2, a curve 200 illustrates an increase and then decrease of the event flow rate with respect to time. Initially, curve 200 crosses a lower threshold 210 at point 214. Thereafter, the event rate peaks and decreases and just touches the lower threshold at point 216 before it begins a climb toward the upper threshold 220. The event curve 200 eventually crosses the upper threshold at 224 while increasing in rate. Thereafter, the event rate peaks and decreases to zero. Along the way, however, the event rate crosses the upper threshold at 228. In the preferred embodiment of the invention, the network element is commanded to suspend the generation of threshold crossing alerts for a period of 600 seconds once the curve crosses threshold 220 at point 224. As may be seen from referring to FIGURE 2, as the event flow rate continues to zero, it crosses the lower threshold 210 at point 218.

In an alternate embodiment of the invention, the crossing of the lower threshold 210 prompts the element management system to generate a message to the cross connect network element 106 that is in a suspended mode of operation to transition back to a normal mode of operation. In the example herein, the upper threshold is defined as ten events per second while

the lower threshold is defined to be three events per second from all of the network elements. It is to be understood that these threshold definitions may readily be varied.

FIGURE 3 is a state transition diagram illustrating two modes of operation for a cross connect network element within a wide area control network 100 of FIGURE 1. In a normal mode of operation, namely state 310, a cross connect network element generates and transmits event information to element management system 104 whenever a specified event is realized. For example, among the hundreds of different types of alarms and messages that may be generated, any one of a large group of quality service messages may be transmitted. Moreover, even within the group of quality of service messages, there are 33 different types of threshold crossing alerts for an existing and known type of cross connect network element. Thus, in the normal mode of operation 310, the cross connect network element 106 continues to generate all 33 types of threshold crossing alerts as necessary.

If, on the other hand, a transition event occurs, namely that a certain event flow rate from the cross connect network elements to the element management systems 104 has been exceeded (event 330), then the cross connect network element that is transmitting the greatest number of the specified alarms is suspended for a period of time from generating more alarms. At this point, the system transitions to state 320.

For example, in the preferred embodiment, if a cross connect network element 106A is generating the greatest number of threshold crossing alerts in comparison to all other cross connect network elements, and if the number of threshold crossing alerts received by element management system 104 exceeds 10 per second from the entire group of cross connect network elements, then the offending cross connect network element 106 is placed into a suspended mode of operation, or state 320. In alternate embodiments of the invention, different types of quality of service messages at different rates or different types of alarms at different rates may be used herein.

Once a cross connect network element is placed into a suspended mode of operation, or state 320, it is no longer allowed to generate a specified type of alarm for a specified period. Rather, the cross connect network element stores the specified type of alarm into memory for uploading at a latter time. By way of example, our cross connect network element 106A might
5 be prevented from generating and transmitting all 33 types of threshold crossing alerts for a period of 600 seconds.

In the preferred embodiment of the invention, a cross connect network element, or state 320 only exits the suspended mode of operation 320 when 600 seconds have expired. Thus, event 350, which is the expiration of the 600 seconds, causes the cross connect network element to transition from a suspended mode of operation, or state 320, to a normal mode of operation, or state 310. Thus, event 340 of FIGURE 3 merely illustrates that the cross connect network element 106A stays within the suspended mode of operation 320 while it has been less than 600
10 seconds since it entered that mode of operation.

In an alternate embodiment of the invention, cross connect network element may transition from the suspended mode of operation, or state 320, to normal mode of operation, or state 310, when the event flow rate reaches or exceeds the lower threshold illustrated in FIGURE 2. By way of example, if the number of threshold crossing alerts from the entire network drops or reaches an event flow rate of 3 per second, the cross connect network element 106A transitions to the normal mode of operation 310 (event 360).
15

It is to be understood that the upper and lower thresholds that trigger the changes in modes of operation from the normal mode of operation 310 to the suspended mode of operation 320 may be varied.
20

FIGURE 4 is a flow chart illustrating a method for controlling an event rate to avoid system degradation according to a preferred embodiment of the invention. Referring now to
25 FIGURE 4, the element management system 104 monitors the event rate from all of the cross

connect network elements (step 404). While monitoring the event rate, the element management system 104 determines whenever the event rate is greater than or equal to a fixed number for a fixed period of time. In the preferred embodiment, the element management system determines when the event rate is greater than or equal to 10 per second from all of the network elements or 1 per second from any one network element (step 408).

Once the element management system determines that the event rate has reached or exceeded 10 per second from all of the network elements or 1 per second for any one network element, it suspends the alarms for the event type for a fixed period of time (step 412). In the preferred embodiment of the invention, the element management system suspends the alarms that relate to the specified event type for a period of 600 seconds by transmitting a signal to EFD 122 to prompt it to “change filters” so as to filter specified types of alarms. In an alternate embodiment, a command is sent to merely restrict the flow of a specified alarm. The element management system then determines when 600 seconds has expired (step 416) and allows the cross connect network element that was instructed to cease transmitting specified alarm types to transition to a normal mode of operation where alarms for the event type are allowed (step 420). Once the system is operating in a normal mode of operation, including the cross connect network element that previously was in a suspended mode of operation, the element management system uploads all alarms that were stored during the suspension period (step 424).

FIGURE 5 is a flow chart illustrating the method in which the element management system monitors the event rate according to one embodiment of the invention. First, the element management system, by way of example, element management system 104 of FIGURE 1, creates a QoS log of events (step 502). In the preferred embodiment, the event log includes quality of service parameters and more specifically, threshold crossing alerts. Thus, as

the specified threshold crossing alerts (quality of service alarms) are received, they are placed into the log created in step 502 (step 504).

In addition to logging the alarm by type, the element management system also records a time value that corresponds to each logged alarm (step 506). The time value allows, at a minimum, the element management system to determine the relative difference in time of alarms. Thus, in one embodiment, the time value is merely a numerical value representing the amount of time that has elapsed since the last logged entry was made. In an alternate embodiment, the time value reflects the actual system time that the alarm was received. The purpose of storing time values is to enable the element management system to determine an event flow rate.

The number of stored events is monitored until it is determined that approximately 1000 have been recorded (step 508). Once the element management system has recorded 1000 entries in the log, it determines the event flow rate for the last events (step 510).

Thereafter, after each alarm is received, once a total of 1000 entries have been placed into the log, the element management system recalculates the event flow rate as a part of monitoring it as described in step 404 and determining when the event rate has reached a specified threshold (step 512).

FIGURE 6 is a flow chart illustrating an alternate embodiment for reducing the rate of event flows, namely the rate of QoS alarms that are transmitted to the element management system. The method disclosed in FIGURE 6 is a method performed in a cross connect network element. First, the cross connect network element receives an indication that the element management system is receiving an excessive number of alarms (step 605).

Typically, a message is received from the element management system indicating that the message flow rate is too high. In the preferred embodiment of the invention, a signal named "off Threshold_Alarms" is used to indicate that the alarm flow rate is too high and that

the cross connect network element is to go into a suspended mode of operation. In this alternate embodiment of Figure 6, however, the cross connect network element responds differently to the specified signal. First, it builds a list of alarms instead of transmitting them (step 610). This step also exists in all preferred embodiments of the invention. Thereafter, the cross connect network element periodically counts the alarms by type that are within the list (step 615). Then, on occasion, the cross connect network element transmits an alarm inventory report to the element management system (step 620). For example, in one embodiment, the cross connect network element may be programmed to transmit the alarm inventory report once every second.

FIGURE 7 is a flow chart that illustrates an alternate embodiment of an inventive method for reducing an event flow rate in a network. Once the element management system determines that an event flow rate has surpassed a defined threshold, it examines a log of received alarms to determine the most common specific type of alarm. Thereafter, it instructs the cross connect network element transmitting the greatest number of the specified alarms to stop transmitting that particular alarm (step 704). If the event flow rate continues to be too high, the element management system will generate a message to prompt the cross connect network element to stop sending that category of alarm (step 708). For example, if the specified type of alarm which was silenced in step 704 was one of the 33 types of threshold alarms, then the category of alarms, namely the threshold alarms, are muted from the one cross connect network element in step 708.

If the event flow rate from that particular cross connect network element is still too high, then the element management system instructs the offending cross connect network element to mute all QoS types of alarms (step 712). Finally, if the event flow rate is still too high, the element management system 104 commands the offending cross connect network element to stop generating alarms at all (step 716). As may be seen, a method illustrated in

FIGURE 7 provides for a graduated set of responses according to the numbers and types of alarms being generated by the cross connect network element that has the excessively high event flow.

The method of FIGURE 7 may be modified in other ways as well. For example, after
5 step 708 in which specified types of QoS alarms are muted, the element management system can instruct the cross connect network element generating the second highest number of event flows to stop transmitting either a specified alarm or a specified type of alarm, for example, the threshold alarms, prior to taking the more drastic step of instructing the first cross connect network element to mute all quality of service alarms. Other variations to reduce the overall
10 event flow rate to the element management system from each of the cross connect network elements 106 of FIGURE 1 may be implemented.

The disclosed invention is particularly advantageous in that it allows an element
management system to mute or partially mute a network element that is generating large numbers of non-critical alarms. Thus, the network's operation is not degraded and threatened
15 with a major failure based on excessive traffic congestion due to the large number of alarms that may be generated as a result of a particular event.

While the invention is susceptible to various modifications and alternative forms,
specific embodiments thereof have been shown by way of example in the drawings and detailed description. It should be understood, however, that the drawings and detailed description
20 thereto are not intended to limit the invention to the particular form disclosed, but on the contrary, the invention is to cover all modifications, equivalents and alternatives falling within the spirit and scope of the present invention as defined by the claims. As may be seen, the described embodiments may be modified in many different ways without departing from the scope or teachings of the invention.

Claims:

1. A method for managing a plurality of network elements, comprising:
receiving a plurality of quality of service (QoS) alarms from the plurality of alarms;
determining an event flow rate wherein an event flow rate is the rate that a specific type
of alarm is received;
determining which of the plurality of network elements is generating the greatest
number alarms; and
instructing the network element generating the greatest number of alarms to stop
sending the alarms.

2. The method of claim 1 wherein the network element does not transmit the
specified types of alarms for a period of 600 seconds.

3. The method of claim 1 wherein only a specific threshold alarm not transmitted
for the period.

4. The method of claim 1 where a type of alarm is not transmitted for the period.

5. The method of claim 4 wherein the type is the threshold types of alarms.

6. The method of claim 4 wherein the type is the QoS types of alarms.

7. The method of claim 1 wherein a network element that has been suspended from transmitting alarms is allowed to start re-transmitting the suspended type of alarm if the event flow has dropped below a lower threshold value.

8. The method of claim 7 wherein the lower threshold value is equal to 3.

9. An element management system, comprising:
a processor;
a store for storing computer instructions that define operational logic of the element management system, the computer instructions for prompting the element management system to issue a signal to a network element to cause it to stop sending QoS signals.

10. The element management system of claim 9 wherein the computer instructions prompt the processor to send a signal to the network element to instruct it to stop sending only a specific type of threshold crossing alarm.

11. The element management system of claim 9 wherein the computer instructions prompt the processor to send a signal to the network element to instruct it to stop sending all threshold crossing alerts.

12. The element management system of claim 9 wherein the computer instructions prompt the processor to send a signal to the network element to instruct it to stop sending all QoS alarms.

1 13. The element management system of claim 9 wherein the computer instructions
2 prompt the processor to send a plurality of signals to the network element to instruct it to stop
3 sending alarms, wherein the instructions to stop transmitting are, in the following order:

4 specified types of threshold alarms;

5 all threshold alarms;

6 all QoS alarms; and

7 all alarms.

1 14. The element management system of claim 9 wherein the computer instructions
2 prompt the processor to send a plurality of signals to the network element to instruct it to stop
3 sending alarms, wherein instructions prompt the element management system to instruct a
4 second network element to stop sending threshold crossing alerts prior to sending an instruction
5 to stop transmitting all QoS alarms.

ABSTRACT

The present invention contemplates an apparatus and a method for limiting the number of specified messages placed onto a network thus to improve network performance. An element management system, upon detecting that a defined threshold has been exceeded for specified types of messages, determines which network element is generating the greatest number of such messages. Thereafter, the element management system instructs the network element that is generating the largest number of alarm messages to cease transmitting a specified type of alarm message. In an alternate embodiment of the invention, if the event flow rate is still too high, the element management system may instruct the cross connect network element to stop sending all threshold types of alarms. Finally, if the event flow rate is still too high, the element management system may cause all QoS alarms from the one network element to not be transmitted. Alternatively, the threshold alarms from other network elements may be muted for a period to reduce the overall event flow rate. For each embodiment, the element management system suspends the flow of messages for a defined period of time. For example, in one preferred embodiment, the select type of QoS signal is muted for a period of 600 seconds. In an alternate embodiment of the invention, a network element is allowed to start transmitting the suspended QoS signals if the overall alarm rate for the suspended QoS signals falls below a lower threshold value.










FIG. 1A





**FIG. 4**

**FIG. 5**

6/7




FIG. 6

7/7




FIG. 7

DECLARATION FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventors (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

**METHOD AND APPARATUS FOR SELF-ADJUSTABLE DESIGN FOR
HANDLING EVENT FLOWS**

the specification of which is being filed herewith.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, ' 1.56(a).

I hereby appoint the following attorneys and/or agents to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, the following:

James A. Harrison

Reg. No. 40,401

Of:

Garlick & Harrison
P.O. Box 67007
Dallas, Texas 75367
Telephone (214) 902-8100
Facsimile (214) 902-8101

AND

V. Lawrence Sewell

Reg. No. 22,753

Joseph E. Rogers

Reg. No. 33,031

Craig A. Hoersten

Reg. No. 38,917

Richard A. Mysliwicz

Reg. No. 40,098

Of:

Alcatel USA Legal Department

Address all telephone calls to James A. Harrison at (214)902-8100, and

002260 26889560

Address all correspondence to:

Alcatel USA
1000 Coit Road
MS LEGL2
Plano, Texas 75075

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of first inventor
(given name, family name): Sandeep Sharma

Inventor's signature: _____

Sandeep Sharma

Date: 9/19/00

Residence: 620 Uvalde Ct.
Allen, Texas 75013

Citizenship: INDIA

Year	1951	1952	1953	1954	1955	1956	1957	1958	1959	1960	1961	1962	1963	1964	1965	1966	1967	1968	1969	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100																					
Population	1,000,000	1,050,000	1,100,000	1,150,000	1,200,000	1,250,000	1,300,000	1,350,000	1,400,000	1,450,000	1,500,000	1,550,000	1,600,000	1,650,000	1,700,000	1,750,000	1,800,000	1,850,000	1,900,000	1,950,000	2,000,000	2,050,000	2,100,000	2,150,000	2,200,000	2,250,000	2,300,000	2,350,000	2,400,000	2,450,000	2,500,000	2,550,000	2,600,000	2,650,000	2,700,000	2,750,000	2,800,000	2,850,000	2,900,000	2,950,000	3,000,000	3,050,000	3,100,000	3,150,000	3,200,000	3,250,000	3,300,000	3,350,000	3,400,000	3,450,000	3,500,000	3,550,000	3,600,000	3,650,000	3,700,000	3,750,000	3,800,000	3,850,000	3,900,000	3,950,000	4,000,000	4,050,000	4,100,000	4,150,000	4,200,000	4,250,000	4,300,000	4,350,000	4,400,000	4,450,000	4,500,000	4,550,000	4,600,000	4,650,000	4,700,000	4,750,000	4,800,000	4,850,000	4,900,000	4,950,000	5,000,000	5,050,000	5,100,000	5,150,000	5,200,000	5,250,000	5,300,000	5,350,000	5,400,000	5,450,000	5,500,000	5,550,000	5,600,000	5,650,000	5,700,000	5,750,000	5,800,000	5,850,000	5,900,000	5,950,000	6,000,000	6,050,000	6,100,000	6,150,000	6,200,000	6,250,000	6,300,000	6,350,000	6,400,000	6,450,000	6,500,000	6,550,000	6,600,000	6,650,000	6,700,000	6,750,000	6,800,000	6,850,000	6,900,000	6,950,000	7,000,000	7,050,000	7,100,000	7,150,000	7,200,000	7,250,000	7,300,000	7,350,000	7,400,000	7,450,000	7,500,000	7,550,000	7,600,000	7,650,000	7,700,000	7,750,000	7,800,000	7,850,000	7,900,000	7,950,000	8,000,000	8,050,000	8,100,000	8,150,000	8,200,000	8,250,000	8,300,000	8,350,000	8,400,000	8,450,000	8,500,000	8,550,000	8,600,000	8,650,000	8,700,000	8,750,000	8,800,000	8,850,000	8,900,000	8,950,000	9,000,000	9,050,000	9,100,000	9,150,000	9,200,000	9,250,000	9,300,000	9,350,000	9,400,000	9,450,000	9,50